




Electrobomba Sumergible Acero Inoxidable / Stainless Steel Pumps AISI 304

X10S-110



Debido a continuas mejoras en los diseños, EMC BOMBAS se reserva el derecho de realizar modificaciones sin previo aviso. Due to continuous improvement in design, EMC BOMBAS reserves the right to amend specifications or data without prior notice.


ISO 9906 Annex A



Características Técnicas

Technical specifications

X10S-110



Difusores <i>Diffuser</i>	: Acero Inoxidable (AISI 304L) : Stainless steel (AISI 304L)
Rodetes <i>Impeller</i>	: Acero Inoxidable (AISI 304L) : Stainless steel (AISI 304L)
Eje bomba <i>Pump shaft</i>	: Acero Inoxidable (AISI 630) : Stainless steel (AISI 630)
Acople <i>Coupling</i>	: Acero Inoxidable (AISI 630) : Stainless steel (AISI 630)
Rejilla <i>Strainer</i>	: Acero Inoxidable (AISI 304) : Stainless steel (AISI 304)
Diámetro Impulsión <i>Outlet connection diameter</i>	: 6" : 6" (inside threaded)

Max. Contenido arena <i>Max. sand content</i>	: 50 gr / m ³ : 50 gr / m ³
Válvula <i>Valve cap</i>	: Acero Inoxidable : Stainless steel
Voltajes <i>Voltage</i>	: 380-415 V (+%6 / -%10) : 380-415 V (+%6 / -%10)
Frecuencia <i>Frequency</i>	: 50 Hz. : 50 Hz.
Temp. Max Agua <i>Max. water temperature</i>	: 30°C (50°C opcional) : 30°C (50°C optional)
Grado Protección <i>Degree of protection</i>	: IP 68 : IP 68

Bombas en AISI 316 también disponibles
Please contact us for optional materials.

Tipo bomba <i>Pump Type</i>	Num. Etapas <i>Stages</i>	Motor		Dimensiones / Dimensions (mm)					Peso / Weight (kg)		
		kW	HP	L	LM	LP	ΦM	ΦP	Motor <i>Motor</i>	Bomba <i>Pump</i>	Total
X10S-110/01	1	7,5	10	1444	758	686	142	213	50	32	82
X10S-110/02	2	15	20	1815	973	842	142	213	72	38	110
X10S-110/03	3	22	30	2103/1887	1106/890	997	142/172	213	87/86	45	132/131
X10S-110/04	4	30	40	2400/2133/2209	1247/980/1056	1153	142/172/192	213	103/103/129	51	154/154/180
X10S-110/05	5	37	50	2656/2369/2425	1347/1060/1116	1309	142/172/192	213	110/113/138	57	167/170/195
X10S-110/06	6	45	60	2604/2666	1139/1201	1465	172/192	213	127/152	64	191/216
X10S-110/07	7	52	70	2838/2906	1218/1286	1620	172/192	213	138/170	70	208/240
X10S-110/08	8	60	80	3117	1341	1776	192	213	185	76	261
X10S-110/09	9	67	90	3298	1366	1932	192	213	186	83	269
X10S-110/10	10	75	100	3478	1391	2087	192	213	195	89	284
X10S-110/11	11	81	110	3714/3613	1471/1370	2243	192/231	213	210/256	95	305/351
X10S-110/12	12	92	125	3935/3829	1536/1430	2399	192/231	213	212/284	101	313/385
X10S-110/13	13	92	125	4090/3984	1536/1430	2554	192/231	213	212/284	108	320/392
X10S-110/14	14	110	150	4220	1510	2710	231	213	311	114	425
X10S-110/15	15	110	150	4376	1510	2866	231	213	311	120	431
X10S-110/16	16	129	175	4632	1610	3022	231	213	338	127	465
X10S-110/17	17	129	175	4787	1610	3177	231	213	338	133	471
X10S-110/18	18	129	175	4943	1610	3333	231	213	338	139	477
X10S-110/19	19	147	200	5229	1740	3489	231	213	370	145	515
X10S-110/20	20	147	200	5384	1740	3644	231	213	370	152	522

Tipo Bomba <i>Pump Type</i>	Num. Etapas <i>Stages</i>	Motor		Inten. <i>Current</i>	m ³ /h <i>l/s</i>	0	70	80	90	100	110	120	130
		kW	HP			(A)	0	19,4	22,2	25,0	27,8	30,6	33,3
X10S-110/01	1	7,5	10	17,2	Altura Manométrica / Head (m)	27	23	22	21	20	18	16	14
X10S-110/02	2	15	20	33,1		55	45	43	42	39	36	33	28
X10S-110/03	3	22	30	48,5		82	68	65	63	59	55	49	43
X10S-110/04	4	30	40	61,7		110	90	87	83	79	73	66	57
X10S-110/05	5	37	50	74,3		137	113	109	104	98	91	82	71
X10S-110/06	6	45	60	90,4		165	135	130	125	118	109	99	85
X10S-110/07	7	52	70	103,3		192	158	152	146	138	128	115	99
X10S-110/08	8	60	80	119,1		220	180	174	167	158	146	131	114
X10S-110/09	9	67	90	134,6		247	203	196	188	177	164	148	128
X10S-110/10	10	75	100	150,7		274	225	217	208	197	182	164	142
X10S-110/11	11	81	110	159		302	248	239	229	217	200	181	156
X10S-110/12	12	92	125	179		329	270	261	250	236	219	197	170
X10S-110/13	13	92	125	179		357	293	283	271	256	237	214	185
X10S-110/14	14	110	150	216		384	315	304	292	276	255	230	199
X10S-110/15	15	110	150	216		412	338	326	313	295	273	247	213
X10S-110/16	16	129	175	248		439	360	348	333	315	292	263	227
X10S-110/17	17	129	175	248		466	383	370	354	335	310	279	241
X10S-110/18	18	129	175	248		494	405	391	375	354	328	296	256
X10S-110/19	19	147	200	282		521	428	413	396	374	346	312	270
X10S-110/20	20	147	200	282		549	450	435	417	394	364	329	284

Debido a continuas mejoras en los diseños, EMC BOMBAS se reserva el derecho de realizar modificaciones sin previo aviso.
 Due to continuous improvement in design, EMC BOMBAS reserves the right to amend specifications or data without prior notice.